

Technical Data Sheet

EPDM® EXT Membrane



Unit 6, Lime Grove Est, Haverhill, Suffolk, CB9 7XU
Tel: 01440 766 975 | www.lynvale.co.uk

EPDM EXT

ELASTOMERIC WATERPROOFING MEMBRANE

EPDM EXT is an elastomeric waterproofing strip based on the rubber polymer EPDM with a low water vapour transmission factor. The product is used as a vapour control layer such as façade waterproofing, damp proof course or similar. The product comes in black colour and has a surface texture on both sides for maximum adhesion. EPDM EXT provides very long expected service life and is an environmentally friendly product.

- ✓ **Elastomeric EPDM Rubber Polymer**
- ✓ **Low Water Vapour Transmission Factor**
- ✓ **Textured Both Sides for Maximum Adhesion**
- ✓ **Very Long Expected Service Life**
- ✓ **Environmentally Friendly Product**
- ✓ **Black Colour Finish**



Ideal Vapour Control & Waterproofing Applications

- ✓ **Effective Vapour Control Layer for Building Envelopes**
- ✓ **Suitable for Façade Waterproofing**
- ✓ **Reliable Damp Proof Course Solution**
- ✓ **CE Certified to EN 14909 & EN 13984**
- ✓ **ATG Approved**
- ✓ **No Limitations in Shelf Life When Stored Correctly**

Material Description	Standards	Classification
Thickness		0.75 mm
Length		25 m
Width		100 - 1700 mm
Weight		0.97 kg/m ²
SD-Value		24 m
Approvals	CE EN 14909, CE EN 13984	ATG Approval
Storage		Cool & Dry, Original Packaging

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes. For detailed product data, please see the corresponding Declaration of Performance. We reserve the right to modify or change the specifications and information without advance notification. All goods are supplied subject to our standard conditions of sale, copies of which are available upon request.