

▶ **2020 5M Fric-Lo® Friction Reduction Tape**

▶ **Hardwearing Abrasion Resistant Tape with Pressure Sensitive Acrylic Adhesive**

2020 5M Fric-Lo® is a highly engineered pressure sensitive adhesive tape, specifically manufactured for critical applications that require an extensive reduction of friction. Once in-situ **2020 5M Fric-Lo®** provides an instant abrasion-resistant, anti-stick, anti-friction surface with operating temperatures up to 107°C (225°F).

2020 5M Fric-Lo® is supplied with a blue filmic inter liner which protects the adhesive during production and storage. The filmic liner removes easily and can be cut using standard scissors.



▶ **Formats**

2020 5M Fric-Lo® is available from Lynvale in finished rolls & bespoke die-cut gaskets.

▶ **Technical Data**

Adhesive Type	Acrylic
Colour	Natural
Total Thickness mm (mil)	0.165 (6.5)
Backing Thickness mm (mil)	0.127 (5.0)
Adhesive Thickness mm (mil)	0.038 (1.5)
Adhesion to Steel N/cm (oz/in)	4.9 (45)
Tensile Strength N/cm (lb/in)	70 (40)
Elongation (% at break)	350
Operating Temperature °C (°F)	-40 to +107 (-40 to +225)

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Lynvale Limited products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Lynvale Limited assumes no responsibility for any product failures that occur due to misuse of the materials or its products arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 6 months, Lynvale Limited warrants this product to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. Lynvale Limited DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

